

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (Currently Amended) A ~~circuit pad~~ system for reducing discomfort caused by a magnetic stimulation device, the system comprising:
a magnetic stimulation device;
a circuit pad;
at least one conductor located on the circuit pad and capable of being used with the ~~a~~-magnetic stimulation device, wherein the conductor is adapted to reduce stimulation induced by the magnetic stimulation device, and.
a connector in communication with the conductor, wherein the connector provides an interface ~~with~~ to the magnetic stimulation device.
2. (Currently Amended) The ~~circuit pad~~ system of claim 1, further comprising a circuit in communication with the conductor.
3. (Currently Amended) The ~~circuit pad~~ system of claim 1, further comprising reducing stimulation by the magnetic stimulation device at a predetermined location.
4. (Currently Amended) The ~~circuit pad~~ system of claim 3, wherein the predetermined location is determined relative to a treatment area.
5. (Currently Amended) The ~~circuit pad~~ system of claim 4, wherein the treatment area is a portion of a brain and wherein the predetermined location is a cutaneous-proximate area relative to the treatment area.
6. (Canceled)

7. (Currently Amended) The ~~circuit pad~~ system of claim 1, further comprising a disposal mechanism that renders the circuit pad inoperable.
8. (Currently Amended) The ~~circuit pad~~ system of claim 7, wherein the disposal mechanism acts automatically upon removal from a patient.
9. (Currently Amended) The ~~circuit pad~~ system of claim 7, wherein the disposal mechanism is activated by a user of the circuit pad.
10. (Currently Amended) The ~~circuit pad~~ system of claim 7, wherein the disposal mechanism changes the physical and electrical properties of the conductor.
11. (Currently Amended) The ~~circuit pad~~ system of claim 7, wherein the disposal mechanism disconnects communication between the conductor and the circuit.
12. (Currently Amended) The ~~circuit pad~~ system of claim 7, wherein the disposal mechanism is activated after a predetermined number of uses.
13. (Currently Amended) The ~~circuit pad~~ system of claim 7, wherein the disposal mechanism permits a certain patient to use the circuit pad for a predetermined period.
14. (Currently Amended) The ~~circuit pad~~ system of claim 13, wherein the predetermined period is a function of a number of uses.
15. (Currently Amended) The ~~circuit pad~~ system of claim 13, wherein the predetermined period is a function of a number of a duration of time.

16. (Currently Amended) The ~~circuit pad~~ system of claim 7, wherein the disposal mechanism destroys the circuit pad upon removal from the patient.

17. (Currently Amended) The ~~circuit pad~~ system of claim 7, wherein the disposal mechanism is constructed of materials that cannot be sanitized.

18. (Currently Amended) The ~~circuit pad~~ system of claim 7, wherein the circuit pad is adapted to become inoperable when contacted with cleaning materials.

19. (Currently Amended) The ~~circuit pad~~ system of claim 7, wherein the circuit pad is constructed of materials that disintegrate when in contact with cleaning solutions.

20. (Currently Amended) The ~~circuit pad~~ system of claim 1, wherein the circuit pad is adapted to be attached to the patient.

21. (Currently Amended) The ~~circuit pad~~ system of claim 1, wherein the circuit pad is adapted to be attached to the magnetic stimulation device.

22. (Currently Amended) The ~~circuit pad~~ system of claim 1, wherein the circuit pad comprises an adhesive.

23. (Currently Amended) The ~~circuit pad~~ system of claim 1, wherein the conductor is a flat metallic device.

24. (Currently Amended) The ~~circuit pad~~ system of claim 23, wherein the conductor is located between two surfaces of the circuit pad.

25. (Currently Amended) The ~~circuit pad~~ system of claim 1, wherein the conductor has an area of in the range of 1 centimeter² to 40 centimeter².

26. (Currently Amended) The ~~circuit pad~~ system of claim 1, wherein the reducing of the stimulation occurs by reducing magnetic flux density created by the magnetic stimulation device.

27. (Currently Amended) The ~~circuit pad~~ system of claim 1, wherein the reducing of the stimulation occurs by superimposing a magnetic field created by the conductors on the circuit pad and a magnetic field created by the magnetic stimulation device.

28. (Currently Amended) The ~~circuit pad~~ system of claim 1, wherein the conductor is provided electrical energy substantially simultaneously with electrical energy provided to the magnetic stimulation device.

29. (Currently Amended) The ~~circuit pad~~ system of claim 28, wherein the electrical energy provided to the conductor and the electrical energy provided to the magnetic stimulation device are of opposite polarity.

30. (Currently Amended) The ~~circuit pad~~ system of claim 28, wherein the electrical energy provided to the conductor is a current that is derived from a voltage provided to the magnetic stimulation device.

31. (Currently Amended) The ~~circuit pad~~ system of claim 1, wherein the circuit pad is adapted to receive a conductive gel that facilitates communication between the circuit pad and a treatment area.

32. (Currently Amended) The ~~circuit pad~~ system of claim 31, wherein the conductive gel is received by an absorbent portion of the circuit pad.

33. (Currently Amended) The ~~circuit pad~~ system of claim 32, wherein the absorbent portion of the circuit pad comprises a sponge material.

34. (Currently Amended) The ~~circuit pad~~ system of claim 31, wherein the conductive gel is located within a plastic material on the circuit pad.

35. (Currently Amended) The ~~circuit pad~~ system of claim 1, wherein the conductor is placed substantially orthogonal to an electric field vector created by the magnetic stimulation device.

36. (Currently Amended) The ~~circuit pad~~ system of claim 1, wherein the conductor has rounded edges.

37. (Currently Amended) The ~~circuit pad~~ system of claim 1, wherein the conductor has a high aspect ratio.

38. (Currently Amended) The ~~circuit pad~~ system of claim 1, wherein a relatively longer dimension of the conductor is placed along a similar direction as an electric field vector induced by the magnetic stimulation device.

39. (Currently Amended) The ~~circuit pad~~ system of claim 1, wherein the conductor is arc-shaped.

40. (Currently Amended) The ~~circuit pad~~ system of claim 1, further comprising insulating material for preventing undesired electrical conduction with the circuit pad.

41. (Currently Amended) The ~~circuit pad~~ system of claim 1, wherein the circuit pad is constructed of a flexible material.

42. (Currently Amended) The ~~circuit pad~~ system of claim 1, wherein the circuit pad is constructed, at least in part, by materials including at least one of the following: plastic, mylar, or polyester.

43. (Currently Amended) The ~~circuit pad~~ system of claim 1, wherein the magnetic stimulation device comprises a magnetic core that saturates at 0.5 Tesla or greater.

44. (Currently Amended) A method for treating a patient using transcutaneous magnetic stimulation, comprising:

directing a magnetic field created by a magnetic stimulation device to a treatment area on the patient;

applying a flexible circuit pad, wherein the flexible circuit pad comprises at least one conductor adapted to reduce stimulation induced by the magnetic stimulation device and a connector in communication with the at least one conductor, ~~the connector providing an interface with the magnetic stimulation device;~~ and

treating the patient with the magnetic field.

45. (Original) The method of claim 44, wherein the magnetic stimulation device comprises a magnetic core that saturates at 0.5 Tesla or greater.

46. (Original) The method of claim 44, further comprising applying the flexible circuit pad to the treatment area.

47. (Original) The method of claim 44, further comprising applying the flexible circuit pad to the magnetic stimulation device.

48. (Original) The method of claim 44, wherein the magnetic stimulation device comprises a magnetic core with a non-toroidal geometry.

49. (Original) The method of claim 44, wherein the conductor reduces stimulation of a cutaneous-proximate area on the patient.

50. (Original) The method of claim 44, further comprising locating the magnetic stimulation device to the treatment area on the patient.

51. (Original) The method of claim 44, further comprising applying the flexible circuit pad to the patient.

52. (Original) The method of claim 44, further comprising applying a conductive gel material between the flexible circuit pad and the patient.

53. (Original) The method of claim 44, further comprising insulating the flexible circuit pad from undesired electrical conduction.

54. (Original) The method of claim 44, further comprising activating a disposal mechanism that renders the flexible circuit pad inoperable.

55. (Original) The method of claim 54, wherein the activating of the disposal mechanism occurs after the patient is treated with the magnetic field.

56. (Original) The method of claim 54, further wherein the activating of the disposal mechanism occurs automatically upon removal from a patient.

57. (Original) The method of claim 54, wherein activating of the disposal mechanism is conducted by a user of the flexible circuit pad.

58. (Original) The method of claim 54, wherein the activating of the disposal mechanism comprises changing the physical and electrical properties of the conductor.

59. (Original) The method of claim 54, wherein the activating of the disposal mechanism comprises disconnecting communication with the flexible circuit pad.

60. (Original) The method of claim 54, wherein the activating of the disposal mechanism occurs after a predetermined number of uses.

61. (Original) The method of claim 44, further comprising adapting the flexible circuit pad to be attached to the patient.

62. (Original) The method of claim 44, further comprising adapting the flexible circuit pad to be attached to the magnetic stimulation device.

63. (Original) The method of claim 44, further comprising applying an adhesive to the flexible circuit pad.

64. (Original) The method of claim 44, further comprising providing a conductive gel that facilitates communication with the flexible circuit pad.

65. (Original) The method of claim 44, further comprising injecting a conductive gel that facilitates communication with the flexible circuit pad.

66. (Previously Presented) The method of claim 44, wherein the circuit pad is constructed, at least in part, by materials including at least one of the following: plastic, mylar, or polyester.

67. (Currently Amended) A ~~circuit pad~~ system for reducing discomfort caused by a magnetic stimulation device, the system comprising:

a magnetic stimulation device for generating therapeutic magnetic stimulation at a first location;

a ferrite material for reducing stimulation on a patient, wherein the ferrite material offsets a magnetic field generated by the magnetic stimulation device ~~capable of being used with the magnetic stimulation device, wherein the ferrite material is adapted to reduce stimulation induced by the magnetic stimulation device~~ at a second location; and

~~a connector in communication with the ferrite material, wherein the connector provides an interface with~~ to the magnetic stimulation device.

68. (Currently Amended) The ~~circuit pad~~ system of claim 67, further comprising a circuit in communication with the ferrite material.

69. (Currently Amended) The ~~circuit pad~~ system of claim 67, wherein the ferrite material is located between two surfaces of the circuit pad.